



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : B42D 15/00	A1	(11) International Publication Number: WO 97/18092 (43) International Publication Date: 22 May 1997 (22.05.97)
---	----	---

(21) International Application Number: PCT/IB96/01140

(22) International Filing Date: 23 October 1996 (23.10.96)

## (30) Priority Data:

95117830.0 13 November 1995 (13.11.95) EP

(34) Countries for which the regional or international application was filed: AT et al.

96105835.1 13 April 1996 (13.04.96) EP

(34) Countries for which the regional or international application was filed: AT et al.

(71) Applicant (for all designated States except US): ORELL FÜSSLER BANKNOTE ENGINEERING LTD. [CH/CH]; Dietzingerstrasse 3, CH-8036 Zürich (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ZINTZMEYER, Jörg [CH/CH]; Rietstrasse 13, CH-8703 Erlenbach (CH). COLEMAN, John, R. [GB/CH]; Bergstrasse 106, CH-8032 Zürich (CH).


(74) Agent: E. BLUM &amp; CO.; Vorderberg 11, CH-8044 Zürich (CH).

(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: SECURITY DOCUMENT WITH SECURITY MARKING



## (57) Abstract

The security marking for security documents, in particular papers representing a value, consists of a plurality of circular or elongate holes (11), which are arranged in parallel rows (14) in a printed area (5) of the document. The diameter (a) of the holes is chosen such that they are practically invisible with bare eyes in reflection, but become well visible when the document (10) is held against a light and viewed in transmission. The holes (11) are generated by laser pulses. The marking can be produced quickly and easily and it can be verified without technical aids.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

Security document with security markingCross References to Related Applications

5

This application claims the priority of European patent applications 95117830.0 filed November 13, 1995 and 96105835.1 of April 13, 1996, the disclosures of which are incorporated herein by reference in their entirety.

10

Technical Field

The invention relates to security documents with security markings, in particular security markings formed by holes, as well as a method for producing same, according to the preamble of the independent claims.

Security documents can be documents representing a value, such as cheques, shares, etc., especially bank notes, but also documents of identification, such as passports, identity cards, access authorisation documents, etc.

20

Background Art

25

In order to make falsification and counterfeiting difficult, security documents are usually provided with security markings, such as watermarks, kinegrams, fluorescent marks, etc. Many conventional marks have, however, the disadvantage that they are difficult to produce or easy to forge and/or that they can hardly be verified without technical equipment by the layman.

30

WO 95/26274 describes a carrier representing a value provided with recognisable patterns formed by holes. The holes are created with a laser beam. The presence of the holes can easily be detected by the eye. However, it is still difficult to verify if the holes are

35

created by a laser or not. To allow verification, it is therefore proposed to make part of the hole patterns so fine that they can only be made visible by means of appliances. This, however, has the disadvantage of requiring special equipment for verification.

### Disclosure of the Invention

Hence, it is a general object of the invention to provide a security document with security markings of this type that are easily verified without special knowledge or equipment. It is also an object of the invention to provide a method for the production of such security documents.

This object is implemented by the document and method of the independent claims.

By using holes having a diameter chosen such that they are invisible when looking at them in reflection while they are visible with the naked eye when viewed in transmission (i.e. when looking through them, e.g. by holding them in front of a source of light), the security marking can easily be verified without special equipment. Holes with this properties preferably have diameters between 85 and 130  $\mu\text{m}$ . In another embodiment, the diameter is between 85 and 115  $\mu\text{m}$ , preferably between 100 and 110  $\mu\text{m}$ .

Holes having these properties can be prepared with laser light (or other suitable radiation) as well as with discharge sparks while they can hardly be created with mechanical means.

The recognisability of the marking is increased when the holes are arranged in an absorbing, substantially completely coloured, printed or coated area. In such an area, the transmission of the document is low and the holes are well visible when holding the document against a light source.

Preferably, the holes have an elongate cross section. Such holes can be produced with a higher rate because the document or the laser beam can be moved while burning the hole. In order to provide elongate holes that  
5 are difficult or impossible to recognise in reflection while they can easily be seen in transmission, the shortest diameter of the holes is preferably between 85 and 130  $\mu\text{m}$ , while the largest diameter is preferably below 170  $\mu\text{m}$ , preferably between 110 and 170  $\mu\text{m}$ , in particular  
10 between 110 and 170  $\mu\text{m}$ .

The security document can e.g. be a banknote, cheque, share, identification document, etc.

Other preferred features are described in the dependent claims.

15

#### Brief Description of the Drawings

The invention will be better understood and  
20 objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings, wherein:

Fig. 1 is a security document according to  
25 the invention, wherein the hole pattern, which is usually not or hardly visible in reflection, is represented by black dots of exaggerated size,

Fig. 2 is a schematic detailed view of the bank note of Fig. 1,

30 Fig. 3 is a schematic representation of a method of production for the security document, and

Fig. 4 is a schematic detailed view of a second embodiment of the holes.

35

Modes for Carrying Out the Invention

In the following, the invention is shown in the embodiment of a bank note. However, it is not limited to bank notes and can be applied to any other type of security document, preferably having a paper carrier, especially documents representing a value and identification documents.

The design of a possible embodiment of the document or bank note 10, respectively, is shown in Figs. 1 and 2. It has been printed in conventional manner with various motifs 1 - 5. In addition to this, it comprises a security marking 6. This marking is represented by exaggerated black dots in Fig. 1. In reality it is practically invisible for the inexperienced observer when viewed in reflection without optical aids. It consists of a two dimensional pattern of holes 11, as they are shown in Fig. 2. Each hole extends through bank note 10. When the bank note is held against the light, the holes 11 can be seen as bright spots with the naked eye, i.e. without the help of any technical equipment.

Since the pattern extends in two dimensions, it can form a sign familiar to the observer, such as a letter or a number. This makes a verification of the marking easier.

As described in detail below, production of the pattern is easier when the pattern is arranged in several, parallel rows 14. However, it is also possible to use a pattern with non parallel rows.

To improve contrast, the whole security marking 6 is arranged in a field 5 of the bank note that is substantially completely coloured, covered with printing or coated, i.e. the colour, printing or coating is either uniform or has a structure much finer than the holes. The optical transmission of the note in this area is therefore low, such that the surroundings of the security

marking 6 appears dark when held against the light while the bright holes 11 are clearly visible.

The area 5 should extend at least over part of security marking 6 (i.e. several holes 11), preferably the whole security marking 6, for providing a good visibility of the marking.

The diameter  $a$  of the holes 11 is preferably in the range of 85 to 130  $\mu\text{m}$ , more preferably between 85 and 115  $\mu\text{m}$ . When using smaller diameters the holes are difficult to recognise and irregularities in the margins of the holes lead to an irregular hole size. When using larger diameters, the holes become visible in reflection. Best results are achieved with diameters around 100 to 110  $\mu\text{m}$ .

The mutual distance  $d$  between the holes should be at least 700  $\mu\text{m}$ . A smaller distance  $d$  weakens the paper and can lead to tears between the holes.

For producing security marking 6, the bank note 10 is e.g. hit simultaneously by several pulsed laser beams 12, such as it is shown schematically in Fig.3. The laser beams are arranged in a row beside each other. The fully printed bank notes 10 are moved individually or in groups on sheets through the beams into a direction 13. Direction 13 is perpendicular to the row of laser beams. The number of laser beams depends on the desired width or numbers of rows 14 of the security marking. By suitable pulse modulation of the laser beams the hole security marking 6 can be generated in a single pass.

The laser source 15 can e.g. be an arrangement of one or more Nd:YAG lasers, because these lasers allow the generation of short pulses and therefore high rates of production.

For applying the security marking 6 to a bank note 10 of pure cotton paper with a thickness between 80 and 95  $\mu\text{m}$  pulses with an energy of 3 - 4 mJ and a duration of 80 ns with a wavelength of 1.064  $\mu\text{m}$  can be used. The laser beams are focused to a theoretical diameter of

20 - 22  $\mu\text{m}$ . The effective Gaussian beam diameter is difficult to measure directly - it is expected to be between 10 and 30  $\mu\text{m}$ .

The holes generated in this way have a typical diameter between 100 and 110  $\mu\text{m}$  independently of any printing present on the note. They are well visible in transmission with the naked eye while they are invisible in reflection. No sharp edges or burs are formed around the holes. The paper's resistance to tearing is not affected.

The security marking according to the invention can be combined with further conventional markings, such as water marks, kinegrams, etc.

For further security, the holes 11 can also be aligned to marks printed on the bank note.

In the above examples, a bank note on a paper carrier has been described. However, the invention can also be used with other carriers, such as plastic carriers.

In the examples shown so far, the holes have a round cross section. However, it is also possible to use holes with a non-round cross section, such as holes with elongate or polygonal cross section.

A preferred embodiment of elongate holes is shown in Fig. 4. The holes shown here have roughly ellipsoidal shape with a shortest diameter  $d_1$  and a longest diameter  $d_2$ .  $d_1$  is preferably in the range of 85 - 130  $\mu\text{m}$ ,  $d_2$  is smaller than 170  $\mu\text{m}$ , preferably 110 - 170  $\mu\text{m}$ . Holes having such a size are barely visible in reflection while being clearly visible in transmission.

The elongate holes 11 are arranged parallel to each other.

Holes of the type shown in Fig. 4 can be generated in an efficient manner by aligning their longitudinal axis with the direction of the relative movement between the notes and the laser beam(s). By moving the notes or beams during application of the laser pulses,



elongate holes are formed automatically. This allows a continues movement of the notes or laser beam(s) during the application of the laser pulses and therefore a larger production rate for a given pulse length.

5           According to a further embodiment of the invention, a single laser beam is used for creating the perforations, which beam is deflected appropriately for generating a desired pattern, which also allows the production of non-parallel rows of holes. It is preferred to  
10 move the paper in one direction while deflecting the laser beam in a direction transversally thereto, such that a similar situation as shown in Fig. 3 results, with the individual beams of Fig. 3 corresponding to different positions of a single laser beam. The deflection allows  
15 the generation of any arbitrary pattern, which can be more complex than a simple row or rows of holes. The laser can e.g. be a CO<sub>2</sub> laser with a wavelength of 10.6  $\mu\text{m}$ . An acousto-optic deflector with high acoustic band width can be used for beam deflection. Furthermore, a fo-  
20 cusing lens is used, the focal width of which is determined in known manner by the diameter of the holes and the properties of the laser beam (beam diameter, beam quality). The speed of the note movement and the pulse repetition rate are adjusted for generating the desired  
25 pattern. Preferably the perforation occurs under a protecting gas, such as nitrogen, which prevents a burning of the notes. The protecting gas can also extend to the focusing lens for preventing contaminations thereon.

          Preferably, a detector is arranged on the  
30 side of the paper facing away from the laser, which detects the laser beam and therefore immediately recognises if a hole has been perforated or not. The sensor is connected to a control unit, which controls the generation of the perforations.

While there are shown and described presently preferred embodiments of the invention, it is to be distinctly understood that the invention is not limited thereto but may be otherwise variously embodied and practised within the scope of the following claims.

Claims

- 5                   1. Security document with a security marking  
(6) for preventing forgery, wherein the security marking  
comprises a plurality of holes (11), which form a pattern  
on the document that is visible in transmission, charac-  
terised in that the diameter (a, d1, d2) of the holes  
10 (11) is such that the pattern is invisible in reflection  
with the naked eye.
2. Security document, of claim 1 characterised  
in that the holes (11) form a two-dimensional pattern on  
the document.
- 15                   3. Security document of any one of the pre-  
ceding claims characterised in that the holes (11) have a  
diameter (a) between 85 and 130  $\mu\text{m}$ .
4. Security document of any one of the pre-  
ceding claims characterised in that the holes (11) have a  
20 diameter (a) between 85 and 115  $\mu\text{m}$ , preferably between  
100 to 110  $\mu\text{m}$ .
5. Security document of any one of the pre-  
ceding claims characterised in that for improving the  
contrast of the pattern visible in transmission the holes  
25 (11) are arranged in an absorbing area (5), which area is  
substantially completely coloured, printed or coated.
6. Security document of any one of the pre-  
ceding claims characterised in that the mutual distance  
(d) of the holes (11) is at least 700  $\mu\text{m}$ .
- 30                   7. Security document of any one of the pre-  
ceding claims characterised in that the holes (11) are  
arranged on several, parallel rows (14).
8. Security document of any one of the pre-  
ceding claims characterised in that it is a document  
35 representing a value, in particular a bank note.

9. Security document of any one of the claims 1 - 7, characterised in that it is a identification document.

10. Security document of any one of the preceding claims characterised in that each hole has elongate cross section with a long and a short axis.

11. Security document of claim 10 characterised in that the long and short axes of the holes (11) are parallel.

12. Security document of any one of the claims 10 or 11 characterised in that said short axis of the holes has a length between 85 and 130  $\mu\text{m}$ .

13. Security document of any one of the claims 10 to 12 characterised in that the long axis of the holes has a length between below 170  $\mu\text{m}$ , preferably between 110 and 170  $\mu\text{m}$ .

14. Security document with security marking (6) for preventing forgery, wherein the security marking comprises a plurality of holes (11), which form a pattern on the document, characterized in that the diameter (a) of the holes (11) is such that, with the naked eye, the pattern is substantially invisible in reflection but visible in transmission.

15. Method for producing a security document with a security marking, wherein for forming said security marking a pattern of holes (11) is created in the document by a laser beam, characterised in that the diameter of the holes is such that, with the naked eye, the pattern is substantially invisible in reflection but visible in transmission.

16. Method of claim 15 characterised in that the laser beam (12) has a wavelength of approximately 1  $\mu\text{m}$ .

17. Method of any one of the claims 15 or 16 characterised in that the laser beam (12) has a wavelength of approximately 10.6  $\mu\text{m}$ .

18. Method of any one of the claims 15 to 17 characterised in that the laser beam (12) is generated by means of a Nd:YAG laser.

19. Method of any one of the claims 15 to 18  
5 characterised in that the laser beam (12) is generated by means of a CO<sub>2</sub> laser.

20. Method of any one of the claims 15 to 19 characterised in that for generating a two dimensional hole pattern the security document is simultaneously hit  
10 with a plurality of laser beams (12).

21. Method of claim 20 characterised in that the laser beams (12) are arranged in a row and the security document of moved perpendicularly to said row.

22. Method of any one of the claims 15 to 21  
15 characterised in that at least one acousto-optic beam deflector is used for deflecting the laser beam from one hole to another.

23. Method of any one of the claims 15 to 22 characterised in that elongate holes are generated by  
20 moving the document and/or the laser beam while burning the holes with the laser beam.

24. Method of any one of the claims 15 to 23 characterised in that a protecting gas is applied while forming the holes for preventing a burning of the security document.  
25




Fig. 1




Fig. 2




Fig. 3




Fig. 4

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 B42D15/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B42D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO,A,95 26274 (INDUSTRIAL AUTOMATION INTEGRATORS) 5 October 1995 cited in the application see the whole document ---	1,14,15
A	US,A,4 939 888 (KATZ ET AL) 10 July 1990 see column 3, line 54 - line 63; figure 5 ---	1
A	DE,U,93 15 294 (HÖLSCHER) 17 February 1994 see the whole document ---	1
A	DE,A,36 34 098 (ÖSTERREICHISCHE NATIONALBANK) 16 April 1987 see the whole document -----	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

20 January 1997

Date of mailing of the international search report

27.01.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Evans, A



# BEST AVAILABLE COPY

## INTERNATIONAL SEARCH REPORT

Inter:      al Application No  
IB 96/01140

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-9526274	05-10-95	NL-A- 9400498 EP-A- 0748286	01-11-95 18-12-96
US-A-4939888	10-07-90	CA-A- 2074494 EP-A- 0537145 EP-A- 0566563 WO-A- 9200878 WO-A- 9210371 US-A- 5087805 US-A- 5107656 US-A- 5137304 US-A- 5197262	07-01-92 21-04-93 27-10-93 23-01-92 25-06-92 11-02-92 28-04-92 11-08-92 30-03-93
DE-U-9315294	17-02-94	NONE	
DE-A-3634098	16-04-87	AT-A- 386159 CH-A- 677290 FR-A- 2588509 GB-A, B 2183544 JP-A- 62094377 US-A- 4740269	11-07-88 30-04-91 17-04-87 10-06-87 30-04-87 26-04-88